



Order no.: 466 605

Product designation:

Half Mask Polimask 330

In connection with respiratory filter (standard thread DIN EN 148-1 and weight of filter <300 g) as filtering device, in connection with powered filtering device as filtering device, in connection with compressed air line device as breathing apparatus. Use filter >300g only in connection with Filter carrying device S/03016.

The scope of protection is determined by the product information, technical standards and valid application rules.



DESCRIPTION

- Adaptability to any kind of face with a good sealing ability
- Low breathing resistance
- Compatible with the use of glasses and goggles
- Easy donning and doffing
- Easy maintenance, washing and disinfection

MAIN FEATURES



Exhalation valve group equipped with compensating pre-chamber

Two-piece harness with adjustable buckles and fasteners

Faceblank made of soft EPDM

Threaded connector conforming with European EN 148/1 standard. For use with one filter series DIRIN 230

PERFORMANCES



Comfort



Ergonomics



Sturdiness



Easy maintenance

APPLICATION FIELDS



Industry



Hospital



Chemical Pharmaceutical Industry



Agriculture

MATERIALS

- Faceblank: Ethylene-Propylene-Diene-Mixture (EPDM)
- Fastener for head harness: Polyamide (PA)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)
- Inhalation valve: Rubber
- Exhalation valve: Rubber
- Exhalation valve fit: Plastic (ABS)
- Exhalation valve cap: Polyphenylene oxide (PPO)
- Connector: Polypropylene (PP)

WEIGHT

- approx.: 145 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Half mask from the Packing and/or Storage container directly before use
- Use the Half mask in accordance with the information brochure

STORAGE

- Ambient temperature. Protect against cold, heat and humidity
- Consider conditions noted on the packaging

CERTIFICATIONS

- The mask is certified according to EN 140
- For use with particle, gas and combined filter of the series DIRIN 230
- Certified according to European Regulation (EU) 2016/425

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

TD 466605 English_06-04.24